



- 1 - Plas-Pro or Timber batten at 400mm centres
- 2 - Plas-Pro or Timber cross battens at 600mm centres
- 3 - 30mm Cladding board fixing
- 4 - Envello Board & Batten Cladding board
- 5 - Junction between cladding boards and Square Edge to be sealed with silicone, the back edge of Square Edge will need to be finished with touch-up coating if visible
- 6 - Square Edge
- 7 - Durafix 45mm fixing
- 8 - Fascia boards, cut down to suit the reveals
- 9 - Durafix 35mm Fixings
- 10 - Perforated Closure
- 11 - Minimum 10mm gap
- 12 - Example window/door detail
- 13 - Example structural timber & sheathing or masonry wall
- 14 - Breather membrane

Note: If treated timber battens are being used, we would recommend putting a strip of DPC, joist tape or epdm on to the front of the battens

**millboard®**

**Live.Life.Outside.**

**Cladding board type:**  
Envello Board & Batten

**Orientation:** Vertical

**Drawing detail:** Window/Door head junction with Square Edge

**Drawing number:** BBV-220-001

**Date:** 10/12/2020

**Drawn By:** SH

**Scale:** NTS

The Millboard Company Ltd  
UK Head Office  
Castle Court  
Bodmin Road  
Coventry CV2 5DB

T: +44 24 7643 9943  
E: [enquiries@millboard.co.uk](mailto:enquiries@millboard.co.uk)  
W: [millboard.co.uk](http://millboard.co.uk)

Company Registered No.06061318  
© The Millboard Company Ltd